



STANDARD SCI SCBA CYLINDERS

Features & Benefits



- Save 30% to 60% off SCBA manufacturer cylinder prices
- Available in 10, 15, 30, 45 & 60 minute durations
- Available in 2216, 3000 & 4500 PSI models
- 15-year service life with 5-year hydrostatic testing
- Millions of units sold – all without ever experiencing a field service failure
- Improved abrasion resistance as compared to other cylinder manufacturers
- Increased fiberglass wrapping improves durability
- Meets or exceeds all Regulatory Technical Standards – DOT & TC approved
- Several models to choose from
- Custom labeling options available
- Available for all SCBAs

Safety + Reliability + Savings = SCI

STANDARD SCI SCBA CYLINDERS

Specifications



STANDARD CYLINDER SPECIFICATIONS

| Model | Approx. Duration (min.) | DOT Approval | TC Approval | PSI | Bar | Volume cu. in. (min.) | Volume liter (min.) | OD inches | OD MM (max.) | OAL inches (max.) | OAL MM (max.) | Weight LBS | Weight KG | Port |
|-------|-------------------------|--------------|-------------|------|-----|-----------------------|---------------------|-----------|--------------|-------------------|---------------|------------|-----------|----------------|
| 374 | 15 | DOT-E 7277 | TC 3FCM | 3000 | 207 | 114 | 2.37 | 4.51 | 114.6 | 11.61 | 294.9 | 3.3 | 1.5 | .750-16 UNF-2B |
| 602 | 30 | DOT-E 10945 | TC SU-5141 | 2216 | 153 | 523 | 8.57 | 6.84 | 173.7 | 19.62 | 498.35 | 6.7 | 3.04 | .750-16 UNF-2B |
| 639 | 30 | DOT-E 10945 | TC SU-5141 | 4500 | 310 | 258 | 4.67 | 5.5 | 139.7 | 19.2 | 487.68 | 6.9 | 3.18 | .875-14 UNF-2B |
| 687 | 30+ | DOT-E 10945 | TC SU-5141 | 3000 | 207 | 515 | 8.44 | 6.82 | 173.2 | 20.44 | 519.18 | 8.3 | 3.76 | .750-16 UNF-2B |
| 603 | 45 | DOT-E 10945 | TC SU-5141 | 4500 | 310 | 416 | 6.82 | 6.86 | 174.24 | 18.2 | 462.28 | 9.3 | 4.23 | .875-14 UNF-2B |
| 695 | 45 | DOT-E 10945 | TC SU-5141 | 4500 | 310 | 412 | 6.75 | 6.32 | 160.5 | 20.47 | 519.94 | 9.75 | 4.43 | .875-14 UNF-2B |
| 604 | 60 | DOT-E 10945 | TC SU-5141 | 4500 | 310 | 550 | 9.01 | 7.19 | 182.6 | 21.2 | 538.48 | 12.2 | 5.53 | .875-14 UNF-2B |

NOTE: Specifications are approximate and subject to change without notice.



www.SCIfireandsafety.com

email: SCIsoba@SCIcomposites.com
 325 Enterprise Place • Pomona, CA 91768
 909.594.7777